

Waxing and Drying Aid

PRODUCT INFORMATION

spray wax for all painted surfaces

Properties:

- * for use in KÄRCHER high pressure cleaner
- * fast drying of the car paint after the cleaning
- * long lasting shine and preservation of paintwork
- * for all automobile paints
- * pH value approx. 5 in concentrate
- * milky liquid with fresh odour

Fields of application:

- * metallic paints
- * paints

Processing:

- fill Waxing and Drying Aid undiluted in the tank of the high pressure cleaner
- dosing 1-3%, apply with low pressure
- do not spray on disks
- rinse with clear water in the high pressure stream for a short time
- go over the car with a chamois

Economy

1 L is sufficient for approx. 3-5 car washes.

Remarks:

- * usable for new paints, wich are basic cleaned.
- * avoid overdosing

1/2 RM 595/3, 10/200



Waxing and Drying Aid

PRODUCT INFORMATION

Attention:

S 2 Keep out of the reach of children.S 23 Do not breathe spray

Further Information:

* Material safety data sheet

Process:

Object: e.g. car paint

- * first prespray the car with RM 555, let react for 2 minutes
- * clean with a high pressure stream, if necessary with a rotating wash brush
- * fill Waxing and Drying Aid undiluted in the tank of the high pressure cleaner
- * dosing 1-3%, apply with low pressure
- * rinse with clear water with the high pressure stream
- * go over the car with a chamois



Alfred Kärcher GmbH & Co. KG

Alfred-Kärcher-Str. 28-40 D-71364 Winnenden Phone +49 (7195) 14-0 Fax +49 (71 95) 14 - 2212 http://www.karcher.com